

Philips Color Kinetics

C-Splash 2

Submersible LED spotlight with intelligent color light



C-Splash 2 is an ultra-thin, submersible luminaire designed to provide vibrant color and color-changing light in water to a depth of 4.6 m (15 ft). With its watertight cast brass housing and silicon bronze adjusting hardware, C-Splash 2 is perfect for water-based applications such as fountains and theme park installations, as well as for applications situated in harsh environments.

- Rugged and watertight—Cast brass housing and yoke with silicon bronze adjusting hardware is designed for submersion in water to a depth of 4.6 m (15 ft). This IP68-rated luminaire is also able to withstand water treated with bromine or chlorine.
- Two beam angles—The frosted tempered glass lens offers a soft-edge beam of light at 22°, while the clear glass lens offers extended light projection at 10°.
- Unified power and data cable—Each C-Splash 2 luminaire comes with a 18.3 m (60 ft) unified power and data cable to minimize wiring. C-Splash 2 is intended for use with PDS-150e and PDS-60 24V power/data supplies.

[Product page](#)

| | |
|------------------|----------------|
| Beam Angle | 10°, 22° |
| Lumens per foot* | 515 to 583 |
| LED Channels | Red/Green/Blue |

[Custom products information available](#)

| | |
|---------------|---|
| Input Voltage | 24 VDC via PDS-150e or PDS-60 |
| Housing | Cast brass |
| Approbations | UL/cUL, FCC Class A, CE, CQC, C-Tick, SAA |
| Environment | Dry/Damp/Wet, IP68 |

Specification Sheets

| PDF Download | Beam Angle | Lumens* | Efficacy | Power | Weight | Item Number | 12 NC |
|----------------------------------|------------|---------|----------|-------|---------------|---------------|--------------|
| 10° Clear Lens | 10° | 583 | 23.3 | 25 W | 10 kg (22 lb) | 116-000024-01 | 910503700617 |
| 22° Frosted Lens | 22° | 515 | 20.6 | 25 W | 10 kg (22 lb) | 116-000024-00 | 910503700616 |

* Lumen output measurements comply with IES LM-79-08 testing procedures.

