



Date: _____ Type: _____

Firm Name: _____

Project: _____

PS-96 24 V

24 V power supply

PS-96 24 V is a power supply for eW® Flex SLX LED lighting fixtures from Philips Color Kinetics. For added control, PS-96 24 V is compatible with the optional eW® Dimming Adapter Kit from Philips Color Kinetics.

Compatible Fixtures

Name	Max. Fixtures Per PS-96
eW Flex SLX	1 string




For device setup details, refer to the Installation Instructions included in the product packaging, or download documentation from www.colorkinetics.com/lsl/pds/ps96/

PS-96 24 V automatically accommodates input voltages ranging from 100 VAC – 240 VAC. The unit includes an IEC North American power cable and output cable with inline 2-pin connector.

Specifications

Due to continuous improvements and innovations, specifications may change without notice.

Item	Specification	Details	
Electrical	Input Voltage	100 – 240 VAC, auto-switching, 50 / 60 Hz	
	Power Output	4.0 A at 24 VDC, 96 W maximum	
Physical	Dimensions (Height x Width x Depth)	1.57 x 2.91 x 6.95 in (40 x 74 x 176 mm)	
	Weight	.77 lb (.35 kg)	
	Construction	High-impact plastic 94V-0 polycarbonate housing	
	Finish	Black matte	
	Connectors	Power Input	IEC 320 C14 AC receptacle, with SVT 18 AWG x 3 power cable
		Power Output	Output cable with inline 2-pin connector for eW fixtures
	Temperature Ranges	14° – 122° F (-10° – 50° C) Operating 14° – 122° F (-10° – 50° C) Startup -40° – 176° F (-40° – 80° C) Storage	
	Humidity	0 – 90%, non-condensing	
Cooling	Convection		
Certification and Safety	Certification	UL / cUL, CE	
	Classification	UL Class 2 power supply	
	Environment	Dry Location, IP20	



PS-96 24 V wiring diagrams are available online at www.colorkinetics.com/support/wiring/



Ordering Information

Item	Included Components	Item Number	Philips 12NC
PS-96 24 V	Power supply, power cable, and Installation Instructions	109-000025-00	910503700109
eW Dimming Adapter Kit	Dimming adapter for eW Cove and eW Flex SLX	107-000007-02	910503700274
2-pin to 4-pin On / Off Adapter	For eW Flex SLX if not using eW Dimming Adapter Kit	107-000008-00	910503700068

Use Item Number when ordering in North America.

PHILIPS



Philips Color Kinetics
3 Burlington Woods Drive
Burlington, Massachusetts 01803 USA
Tel 888.385.5742
Tel 617.423.9999
Fax 617.423.9998
www.philipscolorkinetics.com

Copyright © 2009 – 2010 Philips Solid-State Lighting Solutions, Inc. All rights reserved.
Chromacore, Chromasic, CK, the CK logo, Color Kinetics, the Color Kinetics logo, ColorBlast,
ColorBlaze, ColorBurst, eW Fuse, ColorGraze, ColorPlay, ColorReach, iW Reach, eW Reach,
DIMand, EssentialWhite, eW, iColor, iColor Cove, IntelliWhite, iW, iPlayer, Optibin, and Powercore
are either registered trademarks or trademarks of Philips Solid-State Lighting Solutions, Inc. in
the United States and / or other countries. All other brand or product names are trademarks
or registered trademarks of their respective owners. Due to continuous improvements and
innovations, specifications may change without notice. DAS-000064-01 R01 12-10