



Date:	_Type:
Firm Name:	
Project:	

# eW Dimming Adapter Kit

Dimming adapter for low-voltage EssentialWhite series fixtures



⊕ The eW Dimming Adapter Kit user guide contains configuration details and diagrams. The guide is available online at <a href="https://www.colorkinetics.com/support/userguides/eW\_Cove\_Dimming\_Adapter">www.colorkinetics.com/support/userguides/eW\_Cove\_Dimming\_Adapter</a>



eW Dimming Adapter wiring diagrams are available online at www.colorkinetics. com/support/wiring/

eW® Dimming Adapter Kit provides dimming functionality for select EssentialWhite® low-voltage fixtures, including eW® Flex SLX.

eW Dimming Adapter Kit allows a single 0-10 VDC dimmer (user-supplied) to control up to 72 LED nodes.

- Simple installation eW Dimming Adapter Kit includes easy-to-install components suitable for indoor applications.
- Compact size eW Dimming Adapter mounts inside a standard electrical junction box.
- Dimmer integration eW Dimming Adapter is compatible with commonly available, lowvoltage dimmers.

### Compatible Fixtures

Fixture	Maximum Quantity Per eW Dimming Adapter
eW Flex SLX	1 string



# Specifications

Due to continuous improvements and innovations, specifications may change without notice.

Item	Specification	Details		
Electrical	Maximum Input Voltage	24 VDC, 100 W		
Electrical	Compatibility	0 – 10 VDC dimmers		
	Dimensions (Height x Width x Depth)	$1.2 \times 2.0 \times 4.2$ in $(30 \times 51 \times 107 \text{ mm})$		
	Weight	4.2 oz (119 g)		
Construction		Molded black plastic, steel mounting plate		
Physical	Finish	Black semi-gloss		
	Connectors	Input	2-pin terminal jack for PS-96 24 V power supply from Philips Color Kinetics, or third-party 24 V, 100 W Class 2 UL 1310 listed power supply	
		Output	2-pin terminal block for 0-10 VDC user-supplied dimmer	
			4-pin terminal jack for fixture leader cable	
	Mounting	Fits standard electrical junction box		
	Operating Temperature	14° – 122° F (-10° – 50° C)		
	Humidity	0 – 95%, non-condensing		
Environment	Location	Dry Location, IP20		

# 4.2 in (107 mm) 2.0 in (51 mm) 1.2 in (30 mm)

## Ordering Information

Item	Included Components	Item Number	Philips 12NC
eW Dimming Adapter Kit	eW Dimming Adapter, 30 ft (9.1 m) eW Cove dimming leader cable, 16 AWG DC power cable with flying leads, three-pin terminator, Installation Instructions	107-000007-02	910503700274

Use Item Number when ordering in North America.



Philips Color Kinetics 3 Burlington Woods Drive Burlington, Massachusetts 01803 USA Tel 888.385.5742 Tel 617.423.9999 Fax 617.423.9998 www.philipscolorkinetics.com